



ID 265/55 Afc

Mobile, torque-operated dust extractor RE 201 D 5.5 IE3 for vacuuming medium quantities of dust, fine swarf and hazardous dust (OEL $\geq 0.1 \text{ mg/m}^3$). Robust design.



1 Equipped for dust class M for high occupational safety

- Dust class M filter engineering for vacuuming hazardous dust.



2 Simple and safe emptying without removing the drive head

- Set-down trolley and rolling container for ergonomic emptying.



3 Durable, washable pocket filter and electric filter cleaning

- Uninterrupted vacuuming at high suction power without any reduction in the filter effect.
- Welded seams guarantee long service life of pocket filter.



4 Dust-free emptying system for hazardous materials

- Dust-free emptying thanks to PE sack with integrated closing mechanism.
- Simple disposal of dust in a PE sack.

ID 265/55 Afc

- Automatic filter cleaning system
- Sound reduction

Technical data

Order no.	9.987-208.0	
EAN code	4054278136424	
Current type	Ph / V / Hz	3 / 400 / 50
Air flow rate	l/s / m³/h	738 / 2655
Vacuum	mbar / kPa	47 / 4.7
Container capacity	l	50
Rated input power / Amps	kW	5.5
Filter area	m²	14
Nominal diameter of connection	ID 175	
Sound pressure level	dB(A)	68
Weight	kg	370
Dimensions (L × W × H)	mm	1086 × 1363 × 2667

Equipment

Accessories in scope of delivery	No
----------------------------------	----