IVS 100/75 M

Our most powerful industrial vacuum from the super-class range with dust class M certification: IVS 100/75 M with 7.5 kW side channel blower for very large quantities of dusts that are hazardous to health.

Made in Germany

Order no.	1.573-822.0

- Hygienic stainless steel container
- 100-litre container, filter class M, 7.5 kW drive
- Wear-free side channel blower, user-friendly set-down mechanism

Technical data

EAN code		4054278325644
Number of current phases	**Ph**	3
Voltage	**V**	400
Frequency	**Hz**	50
Air flow	**l/s / m³/h**	156 / 562
Vacuum	**mbar / kPa**	325 / 32.5
Container capacity	**l**	100
Container material		Stainless steel
Rated input power	**kW**	7.5
Vacuuming type		Electric
Connection nominal diameter		DN 70
Accessory nominal diameter		DN 70 / DN 50
Sound pressure level	**dB(A)**	73
Main filter dust class		M
Filter area for main filter	**m²**	2.2
Weight without accessories	**kg**	165
Weight incl. packaging	**kg**	165.8
Dimensions (L × W × H)	**mm**	1202 × 686 × 1465

Equipment

Accessories included in the scope of delivery: no

Container emptying: Set-down trolley

Dust class M

- Complete device certified according to DIN EN 60335-2-69 for dust class M.

Wear-resistant side channel blower

- With 7.5 kW power and soft start for large quantities of dust and solids.
- For strong suction power and service life of at least 20,000 hours.
- Suitable for multiple shift operation and/or with multiple suction points.

Manual IVS filter cleaning

- Effortless operation by means of an ergonomically placed lever if required.
- Extends the life of the filter and thus reduces the maintenance effort.
- Identical cleaning results, regardless of the amount of force used.

IVS 100/75 M, 1.573-822.0, 2026-10-09

KÄRCHER

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

1

2

3

4

5

6

7

8


9


10

11–12

13

14

		Order no.	Description	
FILTERS				
Bag/star filter				
Star filter PE/PTFE M 2.2 m²	1	6.907-651.0		■
EMPTYING SUPPORTS				
Emptying bags				
PE emptying bag dia. 540 mm 100 l	2	9.979-512.0		■
OTHER ACCESSORIES				
Universal accessories holder	3	9.989-789.0	Universal accessories holder for simple storage of suction tubes directly on industrial vacuums from the IVC, IVM and IVS product lines from Kärcher.	■
HANDLES				
Handle stainless steel AISI 304 DN50	4	9.989-897.0		☐
Handle straight stainless steel AISI 304 DN50	5	9.989-899.0		☐
Handle DN50, curved	6	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	☐
Handle DN 70	7	9.977-677.0		☐
Stainless steel handle NW50	8	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	☐
SUCTION TUBES				
Suction tube stainless steel AISI 304 DN50	9	9.989-913.0		☐
Suction tube el. ø50mm IK50 – AK50	10	9.990-934.0		☐
Suction tube 850 mm DN 50	11	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	☐
Suction tube 850 mm DN 70	12	9.981-910.0	Electroconductive extension tube, internal cone DN 70, 850 mm total length.	☐
Aluminium suction tube 1500 mm NW50	13	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	☐
Stainless steel suction tube 850 mm NW50	14	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	☐

■ Included in the scope of supply. ☐ Available accessories.

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

15

16

17

18

19

20

21

22

23

24

25

26

27–28

		Order no.	Description	
ACCESORY SETS				
Accessory kit for liquids				
Liquid/solid accessory kit Expert DN50	15	9.990-879.0	Accessory kit DN50 for liquid vacuums: PU hose 3 m (9.989-619.0), handle (9.977-678.0), standard nozzle (9.988-402.0), surface nozzle 120 mm (9.988-119.0).	☐
Accessory kit for solids/dust				
Food accessory kit Expert DN 50	16	9.989-941.0	Food accessory kit: PU hose 3 m (9.989-973.0), handle (9.989-899.0), standard nozzle (9.989-844.0), brush (9.989-880.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Accessory kit for overhead cleaning DN 50 Expert	17	9.989-943.0	Accessory kit DN 50 for overhead cleaning: suction tubes (9.989-921.0/9.993-009.0), handles (9.989-917.0/9.989-919.0), standard nozzle (9.989-844.0), brush (9.989-880.0), adapter (9.993-011.0).	☐
Accessory kit for solids/dust DN 50 Expert	18	9.989-662.0	Accessory kit DN 50 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-090.0), handle (9.977-678.0), standard nozzle (9.988-402.0), reducer (9.977-772.0).	☐
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA blue DN-F50	19	9.989-841.0		☐
Standard nozzle silicone FDA green DN-F50	20	9.989-842.0		☐
Standard nozzle silicone FDA red DN-F50	21	9.989-843.0		☐
Standard nozzle silicone FDA transparent DN-F50	22	9.989-844.0		☐
Standard nozzle silicone FDA white DN-F50	23	9.989-845.0		☐
Standard nozzle silicone FDA yellow DN-F50	24	9.989-846.0		☐
Standard PVC nozzle DN50	25	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	☐
Standard PVC nozzle DN70	26	9.989-676.0	Electroconductive standard PVC nozzle. DN 70.	☐
Standard nozzle silicone DN50	27	9.988-402.0		☐
Standard silicone nozzle DN70	28	9.989-672.0	Electroconductive standard silicone nozzle. DN 70.	☐

☐ Available accessories.

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

29

30–31

32

33

34

35

36

37

38

39

40

41

42

		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle cuttable rubber DN50	29	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	☐
Standard aluminium nozzle DN50	30	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	☐
Standard aluminium nozzle DN70	31	9.989-663.0	Standard nozzle made from aluminium. Electroconductive. DN 70.	☐
Flexible standard nozzles				
Standard nozzle flexible PVC DN50	32	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	☐
Standard nozzle flexible PVC DN70	33	9.981-422.0	Flexible, electroconductive standard nozzle, DN 70, with rubber mouthpiece.	☐
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F50 blue	34	9.989-862.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 green	35	9.989-864.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 red	36	9.989-866.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 transparent	37	9.989-868.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 white	38	9.989-870.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 yellow	39	9.989-872.0		☐
Floor nozzle stainless steel AISI 316L DN-F50	40	9.989-915.0		☐
Floor nozzle stainless steel 400 mm DN-F50	41	9.989-935.0		☐
Floor nozzle aluminium 400 mm DN-F50	42	9.989-937.0		☐

☐ Available accessories.

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

43–44

45

46

49

50

51

52

53

54

55

56

		Order no.	Description	
NOZZLES				
Floor nozzles				
Aluminium floor nozzle 370 mm DN50	43	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. DN 50.	☐
Aluminium floor nozzle, el, 370 mm, DN50	44	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	☐
Aluminium floor nozzle 500 mm DN50	45	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	☐
Stainless steel floor nozzle el 370 mm DN50	46	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	☐
Crevice nozzles				
Crevice nozzle stainless steel DN50	47	9.989-283.0		☐
Crevice nozzle PP 15 mm × 145 mm DN50	48	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	☐
Crevice nozzle 25 mm × 120 mm DN50	49	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	☐
Stainless steel crevice nozzle 22 mm × 220 mm DN 50	50	9.988-123.0	Stainless steel crevice nozzle, DN 50, suitable for use with foods.	☐
Flexible crevice nozzles				
Crevice nozzle flexible silicone FDA DN-F50 transparent	51	9.989-847.0		☐
Flexible crevice nozzle 12 mm × 45 mm DN50	52	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	☐
Flexible crevice nozzle 20 mm × 45 mm DN50	53	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	☐
Surface nozzles				
Silicone surface nozzle FDA blue DN-F50	54	9.989-850.0		☐
Silicone surface nozzle FDA green DN-F50	55	9.989-852.0		☐
Silicone surface nozzle FDA red DN-F50	56	9.989-854.0		☐

☐ Available accessories.

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

57

58

59

60

61

62

63

64

65

66

67

68–69

70

		Order no.	Description	
NOZZLES				
Surface nozzles				
Silicone surface nozzle FDA transparent DN-F50	57	9.989-856.0		☐
Silicone surface nozzle FDA white DN-F50	58	9.989-858.0		☐
Silicone surface nozzle FDA yellow DN-F50	59	9.989-860.0		☐
Silicone surface nozzle 120 mm DN50	60	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	☐
BRUSHES				
Standard brushes				
Standard brush 40 mm DN50	61	9.981-432.0	Flat brush nozzle DN 50.	☐
End brushes				
Brush FDA blue ø 75 mm DN-F50	62	9.989-874.0		☐
Brush FDA green ø 75 mm DN-F50	63	9.989-876.0		☐
Brush FDA red ø 75 mm DN-F50	64	9.989-878.0		☐
Brush FDA white ø 75 mm DN-F50	65	9.989-880.0		☐
Brush FDA yellow ø 75 mm DN-F50	66	9.989-882.0		☐
Surface brushes				
Surface brush 300 mm DN50	67	9.981-912.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	☐
Cylinder brushes				
Cylinder brush ø 100 mm DN-F50	68	9.989-925.0		☐
Cylinder brush ø 200 mm DN-F50	69	9.989-926.0		☐
HOSES				
PO-Schäuche				
Hose PO el. ø50mm 3m	70	9.990-924.0		☐

☐ Available accessories.

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

71–72

73–76

77

78

79–82

83–84

		Order no.	Description	
HOSES				
PVC				
Hose PVC DN50 3 m	71	9.989-964.0		☐
Hose PVC DN50 5 m	72	9.989-965.0		☐
Hose PVC DN50 3 m	73	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN50 5 m	74	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	☐
Hose PVC DN70 3 m	75	9.989-635.0	Electroconductive PVC hose, DN 70. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN70 5 m	76	9.989-643.0	PVC hose, DN 70. Temperature-resistant up to 85 °C and electroconductive. Length: 5 m.	☐
EVA hoses				
Hose EVA, hose connectors stainless steel, DN 50 3 m	77	9.989-984.0		☐
Hose EVA, hose connectors stainless steel, DN 50 5 m	78	9.989-985.0		☐
Hose EVA NW50 3 m	79	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW50 5 m	80	9.988-091.0		☐
Hose EVA DN70 3 m	81	9.989-613.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 3 m.	☐
Hose EVA DN70 5 m	82	9.989-624.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 5 m.	☐
PU hoses				
Hose PU, hose connectors stainless steel, DN 50 3 m	83	9.989-968.0		☐
Hose PU, hose connectors stainless steel, DN 50 5 m	84	9.989-969.0		☐

☐ Available accessories.

ACCESSORIES FOR IVS 100/75 M
1.573-822.0

85–86

87–90

91–92

93

		Order no.	Description	
HOSES				
PU hoses				
Hose PU FDA, hose connectors stainless steel, DN 50 3 m	85	9.989-973.0		☐
Hose PU FDA, hose connectors stainless steel, DN 50 5 m	86	9.989-974.0		☐
Hose PU DN50 3 m	87	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN50 5 m	88	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
Hose PU DN70 3 m	89	9.989-644.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 3 m.	☐
Hose PU DN70 5 m	90	9.989-645.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 5 m.	☐
ME-PU-hoses				
Hose ME-PU DN70 3 m	91	9.989-646.0	Oil-resistant, electroconductive ME-PU hose, DN 70. Temperature-resistant up to 110 °C, suitable for abrasive suction media. Length: 3 m.	☐
Hose ME-PU DN70 5 m	92	9.989-648.0	Oil-resistant, electroconductive ME-PU hose, DN 70. Temperature-resistant up to 110 °C, suitable for abrasive suction media. Length: 5 m.	☐
ADAPTERS / REDUCERS / DISTRIBUTORS				
Reducers/expanders				
Reducer DN 70 to DN 50	93	9.977-772.0		☐

☐ Available accessories.