# NT 65/2 TACT²

High mobility and power, stamina, robustness and a wide range of practical equipment features make Kärcher Tact² vacuum cleaners sought-after specialists and all-rounders. The NT 65/2 Tact² comes with the full antistatic package as standard. This makes the job much easier in any situation where large quantities of fine dust need to be removed on a regular basis.

Made in Europe

| Order no. | 1.667-286.0 |
|---|---|

- 65-litre container, complete antistatic system, push handle
- Tact² automatic filter cleaning for vacuuming very large quantities of fine dust
- Electrically conductive accessories, 360 mm Adv floor nozzle, Wet & Dry flat pleated filter

## Technical data

| | | |
|---|---|---|
| **EAN code** | | 4039784714953 |
| **Number of current phases** | **Ph** | 1 |
| **Voltage** | **V** | 220 – 240 |
| **Frequency** | **Hz** | 50 – 60 |
| **Air flow** | **l/s** | 2 × 74 |
| **Vacuum** | **mbar / kPa** | 254 / 25.4 |
| **Container capacity** | **l** | 65 |
| **Container material** | | Plastic |
| **Rated input power** | **W** | max. 2760 |
| **Standard nominal width** | | ID 40 |
| **Cable length** | **m** | 10 |
| **Sound pressure level** | **dB(A)** | 73 |
| **Colour** | | Anthracite |
| **Weight without accessories** | **kg** | 24.5 |
| **Weight incl. packaging** | **kg** | 31.3 |
| **Dimensions (L × W × H)** | **mm** | 575 × 490 × 880 |

## Scope of supply

**Suction hose length:** 4 m
**Suction hose type:** electrically conductive
**Bend:** electrically conductive
**Quantity of suction tubes:** 2 Piece(s)
**Suction tubes length:** 550 mm
**Suction tubes material:** Stainless steel
**Wet/dry floor nozzle width:** 360 mm
**Crevice nozzle**
**Drain hose (oil-resistant)**
**Flat pleated filter:** Cellulose fibre material
**Push handle**

## Equipment

**Automatic cut-out features at max. filling quality**
**Antistatic system**
**Filter cleaning:** Automatic Filter Cleaning System Tact²
**Sturdy bumper**
**Protection class:** I
**Stop swivel castor**

### Easy to transport

- Adjustable push handle and large wheels make transport easy even on uneven surfaces.

### Intelligent accessory storage

- For example, the floor nozzle can be quickly fixed any way round.

### Automatic Filter Cleaning System Tact²

- The flat pleated filter can be removed from the clean side; it is divided into two halves, which are cleaned alternately by targeted blasts of air.
- Fine dusts cannot block the filter. A constant high air flow is maintained.
- Over 1000 kg of category A fine dust can be vacuumed without the need to change the filter.

NT 65/2 Tact², 1.667-286.0, 2026-10-09

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0

1

2

3

4

5–7

8

9–11

12

13

14

| | | Order no. | Description | |
|---|---|---|---|---|
| **FLAT PLEATED FILTER, STANDARD, BIA C OR UP TO DUST CLASS M** | | | | |
| **Flat pleated filter, paper** | | | | |
| Dry flat pleated filter, green label, suitable for NT 55/2 Tact², NT 65/2 Tact², NT 75/2 Tact² Me | 1 | 6.907-276.0 | Dry flat pleated filter made from cellulose fibre material with green label for vacuuming fine dust and coarse dirt of dust classes L and M for: NT 55/2 Tact², NT 65/2 Tact² and NT 75/2 Tact² Me. | ■ |
| **Flat pleated filter, PTFE** | | | | |
| Flat pleated filter, PTFE | 2 | 6.907-449.0 | Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. Particularly suitable for very adhesive materials. | ☐ |
| Wet & Dry flat pleated filter, PES fibre material with PTFE coating, suitable for NT 65/2 Tact², NT 75/2 Tact² Me | 3 | 6.907-277.0 | Wet & Dry flat pleated filter made from PES fibre material with PTFE coating with a blue label. Suitable for vacuuming liquids, fine dust and coarse dirt from the M and L dust classes. | ☐ |
| **BENDS** | | | | |
| **Bend, plastic** | | | | |
| Bend, NT, DN 40, plastic, electrically conductive, clip 2.0 at hose end, cone at accessory end | 4 | 2.889-172.0 | Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 2.0 connection at the hose end and a cone connection at the accessory end. | ■ |
| Bend, NT, DN 35, plastic, clip 1.0 at hose end, cone at accessory end | 5 | 5.031-718.0 | DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end. | ☐ |
| Bend, NT, DN 35, plastic, electrically conductive, clip 1.0 at hose end, cone at accessory end | 6 | 5.031-939.0 | Electrically conductive DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end. | ☐ |
| Bend, NT, DN 40, plastic, electrically conductive, clip 1.0 at hose end, cone at accessory end | 7 | 5.032-427.0 | Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end. | ☐ |
| **Bend, other** | | | | |
| Bend, NT, DN 35, chrome-plated metal, cone at hose end, cone at accessory end | 8 | 6.900-519.0 | DN 35 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end. | ☐ |
| Bend, NT, DN 35, stainless steel, cone at hose end, cone at accessory end | 9 | 6.903-141.0 | Robust DN 35 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end. | ☐ |
| Bend, NT, DN 40, chrome-plated metal, cone at hose end, cone at accessory end | 10 | 6.900-276.0 | DN 40 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The robust bend has a cone connection at both the hose end and the accessory end. | ☐ |
| Bend, NT, DN 40, stainless steel, cone at hose end, cone at accessory end | 11 | 6.902-079.0 | Robust DN 40 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end. | ☐ |
| **SUCTION NOZZLES** | | | | |
| **Floor nozzles** | | | | |
| Wet/dry floor nozzle, Adv, DN 40, width 360 mm | 12 | 2.889-153.0 | Plastic Adv floor nozzle with width of 360 mm and nominal size of DN 40 for wet and dry vacuum cleaners from Kärcher. Features brush strips and squeegees that are easy to change. | ■ |
| Wet/dry floor nozzle, DN 35, width 300 mm | 13 | 2.889-173.0 | Plastic floor nozzle in nominal size DN 35 for wet and dry vacuuming of fine dust, coarse dirt or liquids. Features brush strips and squeegees. Width: 300 mm. | ☐ |
| Wet/dry floor nozzle, DN 40, width 360 mm | 14 | 2.889-174.0 | Plastic floor nozzle with width of 360 mm and nominal size of DN 40 for wet and dry vacuuming of fine dust, coarse dirt or liquids. Features brush strips and squeegees. | ☐ |

■ Included in the scope of supply. ☐ Available accessories.

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0

15–17

18

19

20

21

22

23

24

25

26

27

28–29

| | | Order no. | Description | |
|---|---|---|---|---|
| **SUCTION NOZZLES** | | | | |
| **Floor nozzles** | | | | |
| Wet/dry floor nozzle, aluminium, DN 40, width 370 mm | 15 | 6.903-018.0 | Aluminium floor nozzle with rollers, width of 370 mm and nominal size of DN 40 for wet and dry vacuum cleaners from Kärcher. Includes easy-to-replace brush strips and squeegees. | ☐ |
| Wet/dry floor nozzle, aluminium, DN 40, width 450 mm | 16 | 6.906-383.0 | Aluminium floor nozzle with rollers, width of 450 mm and nominal size of DN 40 for wet and dry vacuum cleaning. The brush strips and squeegees that are included are easy to change. | ☐ |
| Wet/dry floor nozzle, aluminium, DN 35, width 370 mm | 17 | 6.906-384.0 | For wet and dry vacuum cleaners from Kärcher: aluminium floor nozzle (DN 35) with a width of 370 mm, including brush strips and squeegees that are easy to change. | ☐ |
| Wet/dry floor nozzle, Adv, DN 40, width 400 mm | 18 | 2.889-117.0 | For wet and dry vacuum cleaners from Kärcher: plastic Adv floor nozzle with width of 400 mm and nominal size of DN 40. Includes easy-to-replace brush strips and squeegees. | ☐ |
| **Crevice nozzles** | | | | |
| Crevice nozzle, NT, DN 40, plastic, 300 mm | 19 | 5.130-655.0 | Plastic crevice nozzle in nominal width DN 40 for Kärcher wet and dry vacuum cleaners. Especially suitable for vacuuming out areas that are difficult to reach, such as joints, crevices and corners. | ■ |
| Crevice nozzle, DN 35, plastic, length 210 mm | 20 | 2.889-130.0 | With the DN 35 plastic crevice nozzle, corners and crevices can be vacuumed quickly and thoroughly. Length: 210 mm. | ☐ |
| Crevice nozzle, NT, DN 35, metal, 500 mm long | 21 | 6.900-922.0 | The metal crevice nozzle (DN 35) enables vacuuming in crevices and corners. Length: 500 mm. | ☐ |
| Crevice nozzle, NT, DN 40, metal, 400 mm | 22 | 6.905-817.0 | Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm. | ☐ |
| **All-purpose brushes** | | | | |
| All-purpose brush | 23 | 6.903-863.0 | Natural bristles (ox hair), bristle element 120 × 45 mm. | ☐ |
| **Car cleaning nozzles** | | | | |
| Car nozzle, ID 40, 90 mm | 24 | 6.900-952.0 | For retrofitting older Kärcher wet and dry vacuum cleaner models with bends in DN 40: Flat angled, convenient, plastic car cleaning nozzle with a working width of approx. 90 mm. | ☐ |
| | 25 | 2.840-095.0 | Flat angled, convenient, plastic, DN 40 car cleaning nozzle specially designed for new Kärcher wet and dry vacuum cleaners with a clip system at the suction hose. Working width: Approx. 90 mm. | ☐ |
| **Rubber suction tools, nose 45°** | | | | |
| Rubber suction tool, nose 45° | 26 | 6.902-104.0 | 45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners. | ☐ |
| NT rubber suction nozzle, bevelled at 45°, DN 40 | 27 | 6.902-105.0 | 45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners. | ☐ |
| **Pipe dusting nozzles** | | | | |
| Pipe brush 35/100 | 28 | 6.903-035.0 | Plastic, pipe diameter 100 mm | ☐ |

■ Included in the scope of supply. ☐ Available accessories.

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0

28–29


30

31–33

34

35

36

37

38

39

40

41

42

| | | Order no. | Description | |
|---|---|---|---|---|
| **SUCTION NOZZLES** | | | | |
| **Pipe dusting nozzles** | | | | |
| Pipe brush 35/200 | 29 | 6.903-036.0 | Plastic, pipe diameter 200 mm | ☐ |
| **SUCTION TUBES** | | | | |
| **Suction tubes, stainless steel** | | | | |
| Suction tube, 2 x, NT, DN 40, 550 mm long, stainless steel, suitable for: NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 75/2 | 30 | 2.889-194.0 | The suction tube set consists of 2 suction tubes made of high-quality stainless steel (DN 40 and 550 mm long each). For Kärcher wet and dry vacuum cleaners. | ■ |
| Suction tube, DN 35, 505 mm, stainless steel | 31 | 6.902-154.0 | Suction tube made of high-quality stainless steel in DN 35 and 505 mm long for wet and dry vacuum cleaners from Kärcher. | ☐ |
| Suction tube, NT, DN 40, 550 mm long, stainless steel, suitable for: AP 100/50, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561, NT 611, NT 802 IV | 32 | 6.902-081.0 | Suction tube made of high-quality stainless steel in nominal width DN 40 and 550 mm long for wet and dry vacuum cleaners from Kärcher. | ☐ |
| Suction tube, NT, DN 40, 1000 mm long, stainless steel, suitable for: NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561, NT 611, NT 802 IV | 33 | 6.906-531.0 | The suction tube made of high-quality stainless steel (DN 40 and 1000 mm long) is suitable for wet and dry vacuum cleaners from Kärcher. | ☐ |
| **Suction tubes, metal** | | | | |
| Suction tube, 2 x, NT, DN 35, 550 mm long, chrome-plated steel, suitable for: NT 27/1, NT 30/1, NT 40/1, NT 50/1, NT 55/1, NT 65/2, NT 75/2 | 34 | 2.889-191.0 | The suction tube set consists of 2 chrome-plated steel suction tubes for Kärcher wet and dry vacuum cleaners, nominal width DN 35 and each suction tube is 550 mm long. | ☐ |
| Suction tube, NT, DN 35, 505 mm long, chrome-plated steel, suitable for: NT 25/1, NT 27/1, NT 30/1, NT 35/1, NT 40/1, NT 48/1, NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/1, NT 75/2, NT 611, NT 802 IV | 35 | 6.900-514.0 | The suction tube made of chrome-plated steel (DN 35, 505 mm long) is suitable for wet and dry vacuum cleaners from Kärcher. | ☐ |
| **SUCTION HOSES** | | | | |
| **Suction hoses with clip system 2.0 (compatible with vacuum cleaners from model year 2017 on)** | | | | |
| Suction hose, NT, DN 40, length 4 m, electrically conductive, clip 2.0, bayonet 2.0 | 36 | 2.889-141.0 | The electrically conductive suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ■ |
| Suction hose, NT, DN 35, length 4 m, electrically conductive, clip 2.0, bayonet 2.0 | 37 | 2.889-137.0 | The electrically conductive suction hose in nominal width DN 35 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher. | ☐ |
| Suction hose, NT, DN 40, length 4 m, clip 2.0, bayonet 2.0 | 38 | 2.889-138.0 | The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 2.5 m, clip 2.0, bayonet 2.0 | 39 | 2.889-139.0 | The suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher. | ☐ |
| Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 2.0, bayonet 2.0 | 40 | 2.889-140.0 | The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher. | ☐ |
| Suction hose, NT, DN 40, length 2.5 m, electrically conductive, clip 2.0, bayonet 2.0 | 41 | 2.889-142.0 | The electrically conductive suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Extension hose, NT, DN 40, length 2.5 m, clip 2.0, connecting adapter | 42 | 2.889-146.0 | The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher. | ☐ |

■ Included in the scope of supply. ☐ Available accessories.

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0

43

44

45

46

47

48

49

50

51

52

53–54

55, 57–58

56

| | | Order no. | Description | |
|---|---|---|---|---|
| **SUCTION HOSES** | | | | |
| **Suction hoses with clip system 2.0 (compatible with vacuum cleaners from model year 2017 on)** | | | | |
| Repair kit for suction hoses DN 40, Clip 2.0 | 43 | 2.889-150.0 | Repair kit ID 40 for the new clip system. | ☐ |
| **Hose connection** | | | | |
| Adapter, ID 32/35, with internal thread | 44 | 6.902-077.0 | Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35. | ☐ |
| Connecting adapter, ID 40, with internal thread | 45 | 6.900-286.0 | Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors. | ☐ |
| **Suction hoses with clip system 1.0 (compatible with vacuum cleaners up to model year 2016)** | | | | |
| Repair kit for suction hoses DN 40 Clip 1.0 | 46 | 2.639-873.0 | Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system. | ☐ |
| Extension hose, NT, DN 40, length 2.5 m, clip 1.0, connecting adapter | 47 | 6.906-344.0 | The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose with bend, NT, DN 40, length 4 m, clip 1.0, bayonet 1.0 | 48 | 4.440-678.0 | The suction hose with bend in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 10 m, clip 1.0, bayonet 1.0 | 49 | 6.906-279.0 | The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 4 m, clip 1.0, bayonet 1.0 | 50 | 6.906-321.0 | The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 1.0, bayonet 1.0 | 51 | 6.906-714.0 | The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose with bend and PFC module, NT, DN 40, length 4 m, electrically conductive, clip 1.0, bayonet 1.0 | 52 | 4.440-728.0 | The electrically conductive suction hose with bend and PFC module in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 16 m, clip 1.0, bayonet 1.0 | 53 | 6.906-635.0 | The suction hose in nominal width DN 40 and with 16 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 10 m, electrically conductive, clip 1.0, bayonet 1.0 | 54 | 6.906-877.0 | The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| **Suction hoses with cone connection** | | | | |
| Suction hose, NT, DN 40, length 4 m, cone, bayonet 1.0 | 55 | 4.440-263.0 | The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 4 m, oil-resistant, cone, bayonet 1.0 | 56 | 4.440-303.0 | The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |

☐ Available accessories.

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0

55, 57–58

59

60

61

62

63

64

65

66

67

68

69

70

| | | Order no. | Description | |
|---|---|---|---|---|
| **SUCTION HOSES** | | | | |
| **Suction hoses with cone connection** | | | | |
| Suction hose, NT, DN 40, length 10 m, cone, bayonet 1.0 | 57 | 4.440-463.0 | The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 10 m, electrically conductive, cone, bayonet 1.0 | 58 | 4.440-466.0 | The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 40, length 10 m, oil-resistant, cone, bayonet 1.0 | 59 | 4.440-612.0 | The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 50, length 4 m, cone, bayonet 1.0 | 60 | 4.440-264.0 | The suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 50, length 3 m, cone, bayonet 1.0 | 61 | 4.440-328.0 | The suction hose in nominal width DN 50 and with 3 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 50, length 10 m, cone, bayonet 1.0 | 62 | 4.440-467.0 | The suction hose in nominal width DN 50 and with 10 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 50, length 4 m, oil-resistant, cone, bayonet 1.0 | 63 | 4.440-613.0 | The oil-resistant suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| Suction hose, NT, DN 50, length 4 m, electrically conductive, cone, bayonet 1.0 | 64 | 4.440-616.0 | The electrically conductive suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners. | ☐ |
| **FILTER BAGS** | | | | |
| **Fleece filter bags** | | | | |
| Fleece filter bags, 5 Piece(s), NT 65, NT 70, NT 72, NT 75, NT 90 | 65 | 2.885-753.0 | Tear-resistant fleece filter bags of dust class M, suitable for Kärcher wet and dry vacuum cleaners. Contents: 5-pack. | ☐ |
| **Paper filter bags** | | | | |
| Paper filter bags, 5 Piece(s), NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC | 66 | 6.904-285.0 | Premium 3-layer paper filter bags of dust class M, suitable for Kärcher wet and dry vacuum cleaners. Contents: 5-pack. | ☐ |
| **FILTER T/ NT** | | | | |
| **Flat pleated filter HEPA, dust class H** | | | | |
| HEPA-14 (H14) flat pleated filter, dust class H, made of glass fibre material | 67 | 6.904-364.0 | For wet and dry vacuum cleaners: HEPA-14 (H14) flat pleated filter made of high-quality glass fibre material. Suitable for vacuuming hazardous dusts, coarse dirt and liquids. | ☐ |
| **Wet filter bag** | | | | |
| Wet filter bag | 68 | 6.904-252.0 | Approved for dust class L, general cleaning, wet and dry, tear-resistant. | ☐ |
| **Fabric filter** | | | | |
| Candle filter Wood, NT 65/2, NT 75/2 | 69 | 2.414-003.0 | Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact vacuums. | ☐ |
| Membrane filter, NT 65, NT 70, NT 72, NT 75, NT 551, NT 602, NT 700, NT 702, NT 802, NT 993 | 70 | 6.904-282.0 | Polyester needle fleece membrane/fabric filter – BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners. | ☐ |

☐ Available accessories.

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0

71

72

73

74–76

77

78

79

80

81, 83

82

84

| | | Order no. | Description | |
|---|---|---|---|---|
| **CONNECTING SLEEVES** | | | | |
| **Y-adapter kit** | | | | |
| Y-adapter kit | 71 | 2.637-217.0 | Plastic distributor – suitable for NT vacuum cleaners. | ☐ |
| **Connection adapter C ID (clip to cone)** | | | | |
| Adapter clip DN 35 on cone DN 35 | 72 | 5.407-005.0 | Adapter clip system DN 35 for connecting suction tubes and small nozzles to cone DN 35. Perfect for vehicle interior cleaning, even without the connection of other nozzles. | ☐ |
| Adapter clip DN 40 to cone DN 40 | 73 | 5.407-006.0 | For connecting small nozzles and suction tubes with cone DN 40: Adapter clip system DN 40. Ideal for vehicle interior cleaning tasks, with no need to connect additional nozzles. | ☐ |
| Connection adapter C DN 35 | 74 | 5.407-112.0 | C 35 hose connector for DN 35 accessory, electrically conductive. | ☐ |
| Electrically conductive DN 40 connection adapter for DN 35 accessories | 75 | 5.407-109.0 | Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners. | ☐ |
| Connection adapter C DN 40 | 76 | 5.407-111.0 | C 40 hose connector for DN 40 accessory, electrically conductive. | ☐ |
| **Connection adapter for power tools, clip connection** | | | | |
| Power tool connection adapter, DN 26-36, electrically conductive | 77 | 5.453-042.0 | 3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners. | ☐ |
| Connection adapter for power tools, C 35, electrically conductive | 78 | 5.453-048.0 | Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums. | ☐ |
| | 79 | 5.453-050.0 | Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums. | ☐ |
| **Adapter for electric power tools, screwable** | | | | |
| Adapter for electric power tools, screwable, ID 35 | 80 | 5.453-016.0 | 3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose. | ☐ |
| | 81 | 5.453-026.0 | Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm. | ☐ |
| | 82 | 6.902-059.0 | Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm. | ☐ |
| | 83 | 6.902-095.0 | 2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm.External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners. | ☐ |
| **Reducing sleeves** | | | | |
| NT reducer from DN 40 to DN 35, electrically conductive | 84 | 5.407-108.0 | Threaded reducer – from C-40 to DN 35. Suitable for NT vacuum cleaners. | ☐ |

☐ Available accessories.

# ACCESSORIES FOR NT 65/2 TACT²
# 1.667-286.0


85

86

87

88

89

90

91

92

93

94

95

| | | Order no. | Description | |
|---|---|---|---|---|
| **CONNECTING SLEEVES** | | | | |
| **Reducing sleeves** | | | | |
| Reducer adapter from DN 40 to DN 35 | 85 | 6.902-017.0 | Reducer, enabling accessories (upholstery nozzle, crevice nozzle, etc.) with a DN 35 connection adapter to be connected to accessory parts (bend or suction tube) that have a DN 40 connection adapter. | ☐ |
| NT reduction bushing with clip system for DN 40 suction hoses on accessory DN 35 | 86 | 5.407-113.0 | Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system. | ☐ |
| Reducer from ID 35 to ID 32 | 87 | 6.902-072.0 | Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners. | ☐ |
| **Reduction/expansion adapter kit** | | | | |
| Set of reducers / adapter sleeves | 88 | 2.860-117.0 | DN 40/35, DN 35/32 (tube -> nozzle), plastic. | ☐ |
| **TARGET-GROUP-SPECIFIC ACCESSORY KITS FOR VACUUM CLEANERS** | | | | |
| Wet and dry vacuuming kit, ID 40, electrically conductive | 89 | 2.638-147.0 | Wet and dry vacuum cleaner set with electrically conductive design, with nominal size 40. | ☐ |
| Car cleaning accessory kit | 90 | 2.862-166.0 | Vehicle interior cleaning accessory kit in nominal width DN 35 for Kärcher wet and dry vacuum cleaners. The kit comprises various nozzles and adapter pieces in nominal widths DN 35 and DN 40. | ☐ |
| **OTHER ACCESSORIES NT** | | | | |
| Cyclone preseparator CS 40 Me | 91 | 2.863-026.0 | The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry. | ☐ |
| Adapter for NT hoses with bayonet connection 1.0 | 92 | 5.031-436.0 | Electroconductive adapter for connecting NT hoses with bayonet 1.0 connection of nominal widths DN 35, 40, 50 to the new accessory system for wet and dry vacuum cleaners from Kärcher. | ☐ |
| **MODIFICATION KIT, NON-CONDUCTIVE MEDIA** | | | | |
| Attachment kit, non-conductive media Tact² + Ap | 93 | 2.642-602.0 | For switching off when vacuuming non-conductive fluids such as oils and greases | ☐ |
| **OTHER ACCESSORIES SCRUBBER DRIERS** | | | | |
| **Miscellaneous** | | | | |
| Extension cable | 94 | 6.647-022.0 | Extension cable, 20 m, 3x1.5 mm². With splash-proof earthing pin plug, strain relief and anti-kink sleeve. | ☐ |
| **EMPTYING SUPPORTS** | | | | |
| **Strainer baskets** | | | | |
| Sieve basket IVC | 95 | 5.731-645.0 | Plastic swarf sieve, perforated, with internal thread. For protecting the drain hose against very abrasive suction material such as coarse shavings. | ☐ |

☐ Available accessories.