IVR 100/60 EF

Large quantities of sand and blasting abrasive, as well as fine swarf and dust, are the areas of application of the IVR 100/60 Ef mobile industrial vacuum cleaner. Ideal for continuous operation in tough industrial applications.

Made in Germany

0–24 h

IE2
HIGH EFFICIENCY MOTOR

Order no.	9.989-405.0

- Convenient, manual discharge flap
- Wear-resistant side channel blower

Technical data

EAN code		4054278695075
Number of current phases	**Ph**	3
Voltage	**V**	400
Frequency	**Hz**	50
Air flow	**l/s / m³/h**	175 / 630
Vacuum	**mbar / kPa**	260 / 26
Container capacity	**l**	100
Rated input power	**kW**	6
Vacuuming type		Electric
Connection nominal diameter		DN 70
Accessory nominal diameter		DN 70 / DN 50
Sound pressure level	**dB(A)**	65
Main filter dust class		L
Filter area for main filter	**m²**	1.75
Weight without accessories	**kg**	250
Weight incl. packaging	**kg**	250.9
Dimensions (L × W × H)	**mm**	1670 × 760 × 1840

Equipment

Container emptying: Emptying flap

IVR 100/60 Ef, 9.989-405.0, 2026-10-09

Convenient, manual discharge flap

- For easy emptying, for example into underfloor conveyors or containers.
- Convenient and time-saving emptying of the suction material, even with large quantities.
- Crane lugs enable safe grabbing and emptying by crane.



Designed for high mechanical stress and versatile in use.

- With practical, movable suction hose port/pipe bend.
- With numerous options for accessory storage.
- The device and chassis are designed for industrial use due to their wall thickness.

Wear-resistant side channel blower

- With 6 kW power and soft start-up for vacuuming large quantities of dust and solids.
- For strong suction power and service life of at least 20,000 hours.
- Optimally suited for mobile use in multiple shift operation.

IVR 100/60 Ef, 9.989-405.0, 2026-10-09

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

2

3

4

5

6

7

8

9

10

11

12

13

14–15

		Order no.	Description	
FILTERS				
Bag/star filter				
Pocket filter 1,75m² Kat "L"	1	9.981-694.0		■
ACCESORY SETS				
Accessory kit for liquids				
Liquid/solid accessory kit Expert DN50	2	9.990-879.0	Accessory kit DN50 for liquid vacuums: PU hose 3 m (9.989-619.0), handle (9.977-678.0), standard nozzle (9.988-402.0), surface nozzle 120 mm (9.988-119.0).	☐
Accessory kit for solids/dust				
Food accessory kit Expert DN 50	3	9.989-941.0	Food accessory kit: PU hose 3 m (9.989-973.0), handle (9.989-899.0), standard nozzle (9.989-844.0), brush (9.989-880.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Accessory kit for overhead cleaning DN 50 Expert	4	9.989-943.0	Accessory kit DN 50 for overhead cleaning: suction tubes (9.989-921.0/9.993-009.0), handles (9.989-917.0/9.989-919.0), standard nozzle (9.989-844.0), brush (9.989-880.0), adapter (9.993-011.0).	☐
Accessory kit for solids/dust DN 50 Expert	5	9.989-662.0	Accessory kit DN 50 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-090.0), handle (9.977-678.0), standard nozzle (9.988-402.0), reducer (9.977-772.0).	☐
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA blue DN-F50	6	9.989-841.0		☐
Standard nozzle silicone FDA green DN-F50	7	9.989-842.0		☐
Standard nozzle silicone FDA red DN-F50	8	9.989-843.0		☐
Standard nozzle silicone FDA transparent DN-F50	9	9.989-844.0		☐
Standard nozzle silicone FDA white DN-F50	10	9.989-845.0		☐
Standard nozzle silicone FDA yellow DN-F50	11	9.989-846.0		☐
Standard PVC nozzle DN50	12	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	☐
Standard PVC nozzle DN70	13	9.989-676.0	Electroconductive standard PVC nozzle. DN 70.	☐
Standard nozzle silicone DN50	14	9.988-402.0		☐

■ Included in the scope of supply. ☐ Available accessories.

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

14–15

16

17–18

19

20

21

22

23

24

25

26

27

28

		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard silicone nozzle DN70	15	9.989-672.0	Electroconductive standard silicone nozzle. DN 70.	☐
Standard nozzle cuttable rubber DN50	16	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	☐
Standard aluminium nozzle DN50	17	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	☐
Standard aluminium nozzle DN70	18	9.989-663.0	Standard nozzle made from aluminium. Electroconductive. DN 70.	☐
Flexible standard nozzles				
Standard nozzle flexible PVC DN50	19	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	☐
Standard nozzle flexible PVC DN70	20	9.981-422.0	Flexible, electroconductive standard nozzle, DN 70, with rubber mouthpiece.	☐
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F50 blue	21	9.989-862.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 green	22	9.989-864.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 red	23	9.989-866.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 transparent	24	9.989-868.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 white	25	9.989-870.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 yellow	26	9.989-872.0		☐
Floor nozzle stainless steel AISI 316L DN-F50	27	9.989-915.0		☐
Floor nozzle stainless steel 400 mm DN-F50	28	9.989-935.0		☐

☐ Available accessories.

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

29

30–31

32

33

36

37

38

39

40

41

42

		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle aluminium 400 mm DN-F50	29	9.989-937.0		☐
Aluminium floor nozzle 370 mm DN50	30	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. DN 50.	☐
Aluminium floor nozzle, el, 370 mm, DN50	31	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	☐
Aluminium floor nozzle 500 mm DN50	32	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	☐
Stainless steel floor nozzle el 370 mm DN50	33	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	☐
Crevice nozzles				
Crevice nozzle stainless steel DN50	34	9.989-283.0		☐
Crevice nozzle PP 15 mm × 145 mm DN50	35	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	☐
Crevice nozzle 25 mm × 120 mm DN50	36	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	☐
Stainless steel crevice nozzle 22 mm × 220 mm DN 50	37	9.988-123.0	Stainless steel crevice nozzle, DN 50, suitable for use with foods.	☐
Flexible crevice nozzles				
Crevice nozzle flexible silicone FDA DN-F50 transparent	38	9.989-847.0		☐
Flexible crevice nozzle 12 mm × 45 mm DN50	39	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	☐
Flexible crevice nozzle 20 mm × 45 mm DN50	40	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	☐
Surface nozzles				
Silicone surface nozzle FDA blue DN-F50	41	9.989-850.0		☐
Silicone surface nozzle FDA green DN-F50	42	9.989-852.0		☐

☐ Available accessories.

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

43

44

45

46

47

48

49

50

51

52

53

54

55–56

		Order no.	Description	
NOZZLES				
Surface nozzles				
Silicone surface nozzle FDA red DN-F50	43	9.989-854.0		☐
Silicone surface nozzle FDA transparent DN-F50	44	9.989-856.0		☐
Silicone surface nozzle FDA white DN-F50	45	9.989-858.0		☐
Silicone surface nozzle FDA yellow DN-F50	46	9.989-860.0		☐
Silicone surface nozzle 120 mm DN50	47	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	☐
BRUSHES				
Standard brushes				
Standard brush 40 mm DN50	48	9.981-432.0	Flat brush nozzle DN 50.	☐
End brushes				
Brush FDA blue ø 75 mm DN-F50	49	9.989-874.0		☐
Brush FDA green ø 75 mm DN-F50	50	9.989-876.0		☐
Brush FDA red ø 75 mm DN-F50	51	9.989-878.0		☐
Brush FDA white ø 75 mm DN-F50	52	9.989-880.0		☐
Brush FDA yellow ø 75 mm DN-F50	53	9.989-882.0		☐
Surface brushes				
Surface brush 300 mm DN50	54	9.981-912.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	☐
Cylinder brushes				
Cylinder brush ø 100 mm DN-F50	55	9.989-925.0		☐
Cylinder brush ø 200 mm DN-F50	56	9.989-926.0		☐

☐ Available accessories.

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

57

58–59

60–63

64

65

66–69

70–71

		Order no.	Description	
HOSES				
PO-Schäuche				
Hose PO el. ø50mm 3m	57	9.990-924.0		☐
PVC				
Hose PVC DN50 3 m	58	9.989-964.0		☐
Hose PVC DN50 5 m	59	9.989-965.0		☐
Hose PVC DN50 3 m	60	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN50 5 m	61	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	☐
Hose PVC DN70 3 m	62	9.989-635.0	Electroconductive PVC hose, DN 70. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN70 5 m	63	9.989-643.0	PVC hose, DN 70. Temperature-resistant up to 85 °C and electroconductive. Length: 5 m.	☐
EVA hoses				
Hose EVA, hose connectors stainless steel, DN 50 3 m	64	9.989-984.0		☐
Hose EVA, hose connectors stainless steel, DN 50 5 m	65	9.989-985.0		☐
Hose EVA NW50 3 m	66	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW50 5 m	67	9.988-091.0		☐
Hose EVA DN70 3 m	68	9.989-613.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 3 m.	☐
Hose EVA DN70 5 m	69	9.989-624.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 5 m.	☐
PU hoses				
Hose PU, hose connectors stainless steel, DN 50 3 m	70	9.989-968.0		☐

☐ Available accessories.

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

70–71

72–73

74–77

78–81

82

83

84

		Order no.	Description	
HOSES				
PU hoses				
Hose PU, hose connectors stainless steel, DN 50 5 m	71	9.989-969.0		☐
Hose PU FDA, hose connectors stainless steel, DN 50 3 m	72	9.989-973.0		☐
Hose PU FDA, hose connectors stainless steel, DN 50 5 m	73	9.989-974.0		☐
Hose PU DN50 3 m	74	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN50 5 m	75	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
Hose PU DN70 3 m	76	9.989-644.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 3 m.	☐
Hose PU DN70 5 m	77	9.989-645.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 5 m.	☐
ME-PU-hoses				
Hose ME-PU DN50 3 m	78	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	☐
Hose ME-PU DN50 5 m	79	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	☐
Hose ME-PU DN70 3 m	80	9.989-646.0	Oil-resistant, electroconductive ME-PU hose, DN 70. Temperature-resistant up to 110 °C, suitable for abrasive suction media. Length: 3 m.	☐
Hose ME-PU DN70 5 m	81	9.989-648.0	Oil-resistant, electroconductive ME-PU hose, DN 70. Temperature-resistant up to 110 °C, suitable for abrasive suction media. Length: 5 m.	☐
HANDLES				
Handle stainless steel AISI 304 DN50	82	9.989-897.0		☐
Handle straight stainless steel AISI 304 DN50	83	9.989-899.0		☐
Handle DN50, curved	84	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	☐

☐ Available accessories.

ACCESSORIES FOR IVR 100/60 EF
9.989-405.0

85

86

87


88

89–90

91

92

93

		Order no.	Description	
HANDLES				
Handle DN 70	85	9.977-677.0		☐
Stainless steel handle NW50	86	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	☐
SUCTION TUBES				
Suction tube stainless steel AISI 304 DN50	87	9.989-913.0		☐
Suction tube el. ø50mm IK50 – AK50	88	9.990-934.0		☐
Suction tube 850 mm DN 50	89	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	☐
Suction tube 850 mm DN 70	90	9.981-910.0	Electroconductive extension tube, internal cone DN 70, 850 mm total length.	☐
Aluminium suction tube 1500 mm NW50	91	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	☐
Stainless steel suction tube 850 mm NW50	92	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	☐
ADAPTERS / REDUCERS / DISTRIBUTORS				
Reducers/expanders				
Reducer DN 70 to DN 50	93	9.977-772.0		☐

☐ Available accessories.