Product data sheet Characteristics

GVAN11

TeSys GV2 and GV3 Manual Starter and Protector, auxiliary contact block, 1 NO and 1 NC, side mount, screw clamp



Product availability: Stock - Normally stocked in distribution facility

Price*: 35.70 USD



Main

TVICAL I		
Range	TeSys	
Device short name	GVAN	
Product or component type	Auxiliary contact block	
Product compatibility	GV2ME GV2RT GV2L GV3P GV3L GV2LE GV2P	
Mounting location	Left side	
Pole contact composition	1 NO + 1 NC	

Complementary

II III nated incodeffice colleges	000 / / III 500	
[Ui] rated insulation voltage	600 V UL 508	
	690 V IEC 60947-1	
	600 V CSA C22.2 No 14	
[Ue] rated operational voltage	48690 V AC	
	24240 V DC	
[lth] conventional free air thermal current	6 A	
Protection type	GB2CB circuit breaker	
•	GG fuse 10 A	
Mechanical durability	100000 Cycles	
Minimum switching current	5 MA	
Minimum switching voltage	17 V	
Rated operational power in VA	300 VA 48 V AC-15 100000 cycles	
·	414 VA 690 V AC-15 100000 cycles	
	500 VA 110127 V AC-15 100000 cycles	
	500 VA 500 V AC-15 100000 cycles	
	650 VA 440 V AC-15 100000 cycles	
	720 VA 230240 V AC-15 100000 cycles	
	850 VA 380415 V AC-15 100000 cycles	

Rated operational power in W	120 W 240 V DC-13 100000 cycles	
Nated operational power in w	140 W 110 V DC-13 100000 cycles	
	140 W 24 V DC-13 100000 cycles	
	180 W 60 V DC-13 100000 cycles	
	240 W 48 V DC-13 100000 cycles	
Tightening torque	12.39 Lbf.In (1.4 N.m) screw clamp terminals	
Height	3.50 ln (89 mm)	
Width	0.37 ln (9.3 mm)	
Depth	2.60 ln (66 mm)	
Net Weight	0.11 Lb(US) (0.05 kg)	

Environment

Environmental characteristic	Normal environment	
------------------------------	--------------------	--

Ordering and shipping details

Category	22367 - MANUAL STR PROTECTOR - GV2
Discount Schedule	l11
GTIN	03389110343489
Nbr. of units in pkg.	1
Package weight(Lbs)	1.62 Oz (46 g)
Returnability	Yes
Country of origin	CZ

Packing Units

· coming come	
Unit Type of Package 1	PCE
Package 1 Height	0.59 ln (1.5 cm)
Package 1 width	2.76 ln (7 cm)
Package 1 Length	3.54 In (9 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	17.99 Oz (510 g)
Package 2 Height	3.74 ln (9.5 cm)
Package 2 width	3.94 ln (10 cm)
Package 2 Length	5.98 ln (15.2 cm)
Unit Type of Package 3	S02
Number of Units in Package 3	60
Package 3 Weight	7.41 Lb(US) (3.36 kg)
Package 3 Height	5.91 ln (15 cm)
Package 3 width	11.81 ln (30 cm)
Package 3 Length	15.75 ln (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes



China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months



Product data sheet Connections and Schema

GVAN11

GVAN11

Product Life Status: Commercialised