




RTR- 380 380 COMBI



Household power supply (220V, 15A)

- Automatic stand-by selective 60/180min, power-off 90/210min & On/off feature for energy saving
- Micronex lamination for pre-cut labels (no additional cutting is required.)
- Automatic motorized pressure system
- GMP digital sleeving® is also available.
- Design of ergonomic horizontality realizing 'all-control-in-one-hand' on front spot for easy operation & convenient film-loading-on.
- Single side and double side lamination
- High gloss lamination
- Hot & cold lamination
- Available wide range jobs
- With multi un/re-winders installed for optimizing performance of Label and photo lamination (RTR-380 COMBI)
- Additional re-winder for cold lamination
- Ergonomic touch screen for enhancing operator-centric convenient control & quality output productivity

TRADE ROLL
LAMINATORS



RoHS



UL-WTDP, CB-TMP Lab.



CE

RTR- 380 series

www.gmp.com

Roll to Roll Laminator

As the best-optimized fit for laminating labels & photos etc., the performance of this machine provides roll to roll lamination solutions for easy & convenient operation that brings high productivity. On top of it, this machine can laminate various kinds of substrate such as metallic foil.

Features

- High glossy lamination
- Hot & cold lamination
- Decurling device for single side lamination
- Microprocessor for pre-programmed functions
- Far-more upgraded productivity by solid & stable mechanism
- Speed & temperature control system with digital mode
- Sleeking solution with auto rewinding device
- Ergonomic touch screen for enhancing operator-centric convenient Control & quality output productivity



Application

- Labels
- Posters, Menu
- Photo Album Covers & Inner pages
- Gift & Greetings cards
- Name card lamination with spot sleeing (Fusing)
- Anti Counterfeit lamination
- Security printing on Gift certificate



Specifications

Models	RTR-380	RTR-380 COMBI
Laminating Speed	7m/min	7m/min
Laminating Width	380mm	380mm
Laminating Films	25mic~250mic	25mic~250mic
Substrate Thickness	80g/m ² ~350g/m ²	80g/m ² ~350g/m ²
Front Roller Diameter	80mm	80mm
Rear Roller Diameter	55mm	55mm
Power Requirements	220~240V, 50/60Hz	AC 220~240V/15A
Power Consumption	3300W, 14.1A	3300W, 14.1A
Warm up Time	7 minutes	7 minutes
Heating System	Hot Roller Internal Infrared Heater	Hot Roller Internal Infrared Heater
Operating Temperature	150°C Max.	150°C Max.
Speed Control	Touch panel	Touch panel
Temperature Control	Touch panel	Touch panel
Film Core	77mm(3"dual)	77mm(3"dual)
Colling System	Blower	Blower
Dimensions(WxLxH)	650 x 955 x 500mm	650 x 1205 x 510mm
Type of Main Motor	DC W-Geared Motor	DC W-Geared Motor
Type of Rewinder Motor	Linked to Main Motor	Linked to Main Motor

※ GMP reserves the right to change specifications without prior notice.