

PRESSURE SCREEN

Certification Sheet

VOITH SULZER

PAPER TECHNOLOGY

2620 E. Glendale Ave.

Appleton, WI 54915

Telephone (920) 731-7724

Telefax (920) 731-0240

IDENTIFICATION	CUSTOMER <u>Inter Lake Papers, Inc.</u> ADDRESS (ORDER) <u>Wisconsin Rapids, WI</u> ADDRESS (INSTALL) <u>Kimberly, WI</u> CUST. ORDER NO. <u>79504314X13</u> CUST. EQUIP. NO. _____ CERTIFIED BY <u>Fritz Wenzel</u> FRITZ WENZEL	SIZE & TYPE <u>Vertical Screen AFVPS20</u> CUST. DESIGNATION _____ SERIAL NO. (S)* <u>21833</u> VOITH SULZER JOB NO. <u>50902</u> ORDER DATE <u>7/16/99</u> TITLE <u>PRODUCT ENGINEER</u>
APPLICATION	INSTALLATION DWG. <u>D36-130164/A</u> BSKT DWG. <u>07.2026.30</u> BSKT TYPE <u>C-bar</u> P/N <u>07.1180.90</u> STOCK TO BE HANDLED <u>White Water</u> FREENESS <u>100 CSF @ Headbox</u> PH VALUE <u>7.8</u> STOCK TEMP. <u>120° F</u> SCREEN FED BY _____ ACCEPTS DISCH. TO <u>Dilution Header</u> SCREEN PERF. DIA.: <u>N/A</u> IN <u>N/A</u> MM SLOT WIDTH <u>0.008</u> IN <u>0.20</u> MM ROTOR DWG. <u>D36-300002</u> ROTOR SPEED <u>351RPM</u>	CONSISTENCY <u>0.29%</u> THROUGHPUT <u>51</u> BDSTPD <u>3,000</u> GPM IMPURITIES IN STOCK _____ SEAL TYPE <u>MECHANICAL</u> REJECTS DISCH. TO <u>Thick Stock Screening</u> OPEN AREA <u>5.0%</u>
MATL	WETTED PARTS: CAST <u>316</u> WELDED <u>316L</u>	
DRIVE	DRIVE BY <u>Voith Sulzer</u> MOTOR SHEAVE <u>4GR</u> DRIVEN SHEAVE <u>4GR</u>	V-BELT/POWERBAND NO. <u>4/5VX1800</u> C.D. <u>54.6"</u> <u>5V 12.5" O.D. BORE 3.38 KW 0.88 x 0.06</u> <u>5V 31.5" O.D. BORE 3.31 KW 0.88 x 0.19</u>
MOTOR	MOTOR BY <u>Customer</u> FRAME <u>444T</u> HP <u>75</u> RPM <u>900</u> VOLTS _____ PHASE <u>3</u> HERTZ <u>60</u> MOTOR SHAFT DIA. <u>3.38</u> KW <u>0.88 x 0.44</u> ELEVATION _____	
OPTIONS	<u>FURNISHED ONLY IF MARKED</u> ☒ METAL TO METAL ACCEPTS FLANGE ☒ METAL TO METAL INLET FLANGE ☐ ELECTROPOLISH PRESSURE GAUGES: ☐ PORT PLUGS ☐ LOCAL ☐ REMOTE	
REMARKS	*ALWAYS SPECIFY UNIT SERIAL NO. WHEN ORDERING SPARE PARTS.	