



MODEL 75

SPECIFICATIONS

OVEN MODEL	75-12	75-16	75-20	75-24	75-36
Bun Pans (18"x26")	12	16	20	24	36
Bread Loaves (5"x9")	96	128	160	192	288
Height	6' 7"	6' 7"	6' 7"	6' 7"	7' 10"
Width	7' 2"	8' 10"	10' 2"	11' 6"	11' 6"
Depth	7' 4"	7' 4"	7' 4"	7' 4"	8' 9"
Weight Lbs.	5500	6000	6500	7550	7900
Height of Loading Door from Floor	44"	44"	44"	44"	44"
Clearance between Trays	11"	11"	11"	11"	11"
Max. BTU's reqd.	160,000	200,000	240,000	270,000	400,000
Size Gas Line reqd.	3/4"	3/4"	1"	1"	1 1/2"
Diameter Exhaust Stack	6"	9"	9"	9"	9"
Diameter Door Vent Flue	4"	6"	6"	6"	6"
Electric Heating KW	28	33	40	48	70

Standard Electrical Specifications : A.C. 115V 1Ph 60Hz
Optional: 230V 3Ph 60Hz (D.C and special voltages extra charge)

STANDARD FEATURES

STAINLESS STEEL FRONT AND TWO CORNERS

BAKE TIMER

PUSH BUTTON DRIVE

TRAY INDICATOR

INDICATING AND REGULATING THERMOSTAT

EXPANDED METAL OR SOLID STEEL TRAY HEARTHS

ATMOSPHERIC GAS BURNER WITH COMBUSTION SAFEGUARD

DUAL GAS VALVES

FISH EXCLUSIVE FLUID DRIVE

INTERIOR OVEN LIGHT

6" THICK ROCK WOOL INSULATION ON SIDES

8" ROCK WOOL INSULATION ON TOP

LONG LIFE HIGH TEMP. CARBON BUSHINGS

INTERNAL DRIVE

FRONT SERVICE ACCESS

OPTIONAL FEATURES

USDA APPROVED*

AUTO TRAY STOP

VERTICAL RISING BAKER DOOR (S)

BAKER WINDOWS

SPECIAL TRAY SIZES - (6 TRAYS 20") OR (5 TRAYS 23")

DUAL PUSH-BUTTON DRIVE

PREMIX LINE BURNER

TYPE II HOOD

SOLID STEEL OR EXPANDED METAL TRAYS

NATURAL OR L/P GAS

SPECIAL VOLTAGE

PRISON PACKAGE

ADD- A- TRAY (2EA)

STEAM LINES & TRAP (REQUIRES PREMIX BURNER)