

## 618L • 624 • 634

### Open Kettle Electric Fryers

Belshaw open kettle electric fryers are designed to efficiently produce all varieties of cake donut and yeast raised donut. Almost any size and shape of donut can be made in these adaptable and dependable fryers.

- **Compact.** The space needed to operate a Belshaw 618L electric fryer is 6 feet x 3½ feet (180 x 110 cm), including cake donut depositor and open drain tray. Larger models need appropriate increased space allowance.

- **Productive.** 60, 90 or 120 dozen standard size donuts/hour @ 120 second frying time.

- **Robust.** Heavy duty heating elements used by Belshaw electric fryers are robust enough to withstand daily use over an extended period of years.

- **Convenient.** The elements tilt up vertically to allow quicker cleaning. The kettle can be easily removed. A turn of the exterior handle opens the drain to filter shortening.

- **Designed to work together.** With a Belshaw Open Kettle donut system, the fryer, cake donut depositor, and filtration system are designed to work together. An easy-to-use submerger can be added to further improve production efficiency.

- **Electronic temperature controller.** The electronic controller maintains temperature within a narrow band, and displays current temperature and set temperature at all times.

- **Belshaw provides a full line of companion equipment** designed for donut production:


- Type B or Type F cake donut depositors
- EZ Melt Filtration system
- CP Cabinet Proofer
- H&I-2 or H&I-4 Icing Tables
- HG or HGEZ Hand Glazers



624 Electric Fryer with optional EZMelt 24 filtration system

#### 618L


Holds up to  
**24 donuts**  
Capacity up to  
**60 dozen/hour**



**26"**  
**(66cm)**  
**18" (46cm)**

#### 624


Holds up to  
**36 donuts**  
Capacity up to  
**90 dozen/hour**



**24"**  
**(61cm)**  
**24" (61cm)**

#### 634

Holds up to  
**48 donuts**  
Capacity up to  
**120 dozen/hour**



**24"**  
**(61cm)**  
**34" (86 cm)**




WEB



VIDEO

\*Capacity measured @120 seconds fry time with standard size donuts.



### CLEARANCES

Between fryer and any construction:

BACK:  
6 inches (153 mm)

SIDES:  
2 inches (51 mm)

LEFT:  
24 inches (635mm) clear space recommended if cake donut depositor is used. (Can be changed to right side).

### STANDARD FEATURES

- Stainless steel cabinet, kettle, and drain tray, with sloping surface around fryer kettle.
- Drain tray, field reversible either side.
- Heavy duty elements, tiltable upwards for easy kettle cleanup.
- Highly accurate electronic temperature controller, located on fryer door.
- High-temperature limit switch.
- Two nickel plated cake donut frying screens with bolt-on heat dissipating handles.
- Adjustable, bolt down legs.
- Heavy duty drain and valve with exterior handle.
- Reinforced side panel to accept Belshaw cake donut depositor mount. (Field reversible)

### OPTIONS AND ACCESSORIES

- Submerger.
- Proofing screens (screens without handles for yeast raised donuts).
- Detachable handles OR Screen Cradle, for lifting screens from fryer.
- Type B (manual) or Type F (electric) cake donut depositor.
- EZMelt filtration system.

### VENTILATION AND FIRE SUPPRESSION

- Customer is responsible for installation of ventilation hood and/or fire suppression as required by local codes.

### CERTIFICATIONS

- 208-240/60/1 and 208-240V/60/3 models: Certified to UL-197, CSA C22.2 and NSF-4.
- CE models available.

### SPECIFICATIONS

		618L	624	634
<b>FRYING AREA</b>	inches	18" x 26"	24" x 24"	34" x 24"
	cm	46 x 66 cm	61 x 61 cm	86 x 61 cm
<b>SCREEN SIZE</b>	inches	17" x 25"	23" x 23"	33" x 23"
<b>SHORTENING CAPACITY (approx)</b>	lbs	82 lbs	96 lbs	197 lbs
	kg	37 kg	44 kg	90 kg
	gallons	11 gal	13 gal	26.5 gal
	liters	42 L	49 L	100 L
<b>ELECTRICAL DATA (specify voltage at time of order)</b>				
<b>208-240V, 50/60hz, 1ph</b>	amps	46 - 53 A	70 - 78 A	
	kilowatts	9.6 - 12.7 KW	14.1 - 18.7 KW	
<b>208-240V, 50/60hz, 3ph</b>	amps		39 - 45 A	51 A - 59 A
	kilowatts		14.1 - 18.7 KW	18.3 - 24.4 KW
<b>380-415V, 50/60hz, 3ph</b>	amps	49 - 54 A	18 - 26 A	
	kilowatts	10.8 - 12.8 KW	11.9 - 18.7 KW	
<b>ELECTRICAL CORD/PLUG</b>	Not supplied			
<b>WIDTH (A)</b> <i>(drain tray CLOSED)</i>	inches	27"	32"	40.5"
	cm	69 cm	81 cm	103 cm
<b>WIDTH (B)</b> <i>(drain tray OPEN)</i>	inches	48"	56"	75"
	cm	122 cm	142 cm	191 cm
<b>DEPTH (C)</b>	inches	38"	36"	36"
	cm	97 cm	92 cm	92 cm
<b>HEIGHT (D)</b>	inches	40"	40"	40"
	cm	102 cm	102 cm	102 cm
<b>SHIPPING DIMENSIONS</b> <i>(crate)</i>	inches	40"x48"x54"	40"x48"x54"	51"x45"x56"
	cm	102x122x137	102x122x137	130x114x143
<b>SHIPPING WEIGHT</b>	lbs	260 lbs	275 lbs	385 lbs
	kg	118 kg	125 kg	175 kg
<b>FREIGHT CLASS</b>		100	100	100