



# TS-516

## THE **ULTIMATE** TOUGH SCREENING SOLUTIONS

The TS-516 track scalping screening plant is ideal for heavy-duty applications that require screening of materials such as recycled concrete, iron ore and aggregates. The unit can also be used in crusher circuits. This robust, versatile machine handles sticky clay and topsoil and can process up to 570 TPH.





TS-516



ENGINE	129-horsepower CAT® C4.4 (Tier 3)
HOPPER CAPACITY	11.7 cubic yards
STOCKPILE HEIGHT	14 feet, 1 inch
TOP DECK	16 feet by 5 feet
BOTTOM DECK	15 feet, 4 inches by 5 feet
DISCHARGE CONVEYOR	63 inches wide with impact bed
WEIGHT	77,175 pounds



## FEATURES

A 63-inch-wide discharge conveyor, the widest in the industry, reduces jamming at the screen's discharge point.

The heavy-duty, direct-feed system includes a rubber belt feeder and an optional Hardox® apron feeder for increased longevity in rigorous applications.

Three hydraulic, folding side conveyors allow easy transport and set-up times of 10 minutes or less.

With a high-energy, two-bearing, 16-foot by 5-foot screen box, the TS-516 offers 157 square feet of screening area and the ability to sort up to three different product sizes. Optional top deck bofar bars, top deck punch plate, heavy-duty top finger deck and bottom finger deck prolong screen and crusher life in rugged applications.

**IROCK** 5531 CANAL ROAD, VALLEY VIEW, OH 44125

Phone: 866-240-0201 • Fax: 440-735-4974 • Email: [sales@irockcrushers.com](mailto:sales@irockcrushers.com)

[www.irockcrushers.com](http://www.irockcrushers.com)

IROCK™ is a trademark of IROCK Crushers, LLC.  
CAT® is a registered trademark of Caterpillar Inc.  
Hardox® is a registered trademark of Hardox Wearparts.