



# ◀◀◀◀◀◀◀◀ DZ516TK

---

## TRACKED TROMMEL

---

The DZ516TK trommel is all about producing the highest quality materials. Diamond Z offers a wide range of drum designs and screen sizes to improve quality and meet high demand. Material such as topsoil, compost, sand and gravel and wood chips spend more time in the 16' foot drum for better screening results.

The three screen sections allow for flexibility in sizing to maximize productivity, while the hydraulically folding end conveyor lets oversize material to be effectively stockpiled.

For heavy-duty applications, a remote control hydraulic tipping grizzly can be added to scalp off large material.

---

## FEATURES

---

- ◆ 5' x 16' (1.5m x 4.9) heavy duty trommel drum
- ◆ Tracked mobility
- ◆ Integrated hydraulic folding stockpiling conveyors
- ◆ Radial remote controlled conveyor
- ◆ 10 minute setup time
- ◆ Large engine bay
- ◆ Hydraulic tipping grid option





#### BRUSHES

Ground level adjustable brushes keep the screen clean and rotate away from drum for ease of drum change.

#### HOPPER CAPACITY

Hopper capacity of 4.5yd<sup>3</sup> (3.4m<sup>3</sup>) with extensions for greater efficiency.

#### RADIAL CONVEYOR

Radial conveyor offers the trommel a 15' 1" (4.6m) stockpile height.



#### TROMMEL DRUM

Features a 5' x 16' (1.5m x 4.9m) steel drum, with numerous drum and screen options available.

#### TRACKED MOBILITY

Tracked unit with 4 outriggers for leveling.

SPECIFICATIONS		DZ516TK	
Engine	100hp (74kw)	Working Length	85' 8" (26.12m)
Transport Height	13' 7" (4.14m)	Hopper Capacity	4.5yd <sup>3</sup> (3.4m <sup>3</sup> )
Transport Length	52' 6.5" (16.01m)	Drum	5' x 16' (1.52m X 4.88m)
Transport Width	9' 6" (2.90m)	Radial Conveyor	15' 1" (4.6m)
Weight	36,000 lbs (16,330 kg)	Oversize Conveyor	10' 1" (3.8m)
Working Height	15' 8" (4.78m)		

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.