

6203LPPM

Portable Screen Plant



6203-32LP Screen

- 6' x 20' triple deck
- Aggressive stroke triple shaft horizontal
- Fully adjustable timing angle, stroke length, and stroke speed to fit most applications
- 40HP 1,200 RPM TEFC electric motor
- Bolt on feedbox with 1/4" AR liners
- Fully contained oil lubrication assembly
- Rubber marshmallow springs reduce basket stress
- Multiple deck configurations

Under Screen Conveyor

- 60" Under screen conveyor
- Grade II, 330 3 ply belting
- 10hp electric motor

Discharge Chutes

- Straight discharge chutes for all decks
- AR lined

Chassis

- Heavy-duty structural I-beam
- Tandem axle Hutch suspension
- Under screen collection hopper - AR lined
- Fold down catwalks on both side of the plant
- Fifth wheel pin
- Four jacking pads
- Air brakes
- Stop-tail-turn and running lights
- 11.00x22.5 radial tires
- Mudflaps
- Safety guards

Options

- Blending chutes
- Roll away blending chutes
- Cross conveyors
- Cross conveyors with blending chutes
- Switchgear w/starters for screen drive and on plant motors
- Telescoping support leg
- Hydraulic lifting jacks
- Stabilizing System
- Stabilizing system (4) cylinder, 24" "run on" design, with either 8HP gas, 5HP electric, 12V, or 24V power unit
- Vulcanized belt

Physical/Operating Characteristics

Dimension	Standard	Metric
Operating Length	38' 5"	11.6m
Operating Height	13' 6"	4.1m
Travel Height	13' 6"	4.1m
Travel Width	9' 11 3/4"	3m
Feed Height	13' 6"	4.1m
Max Feed Size Up To	10"	254mm
Max Top Deck Opening	4"	102mm
Max Drop of Feed	18"	458mm
Estimated Dual Axle Weight*	42,600lb	19,323kg

**Depending on options, consult factory for specific applications.*