

HORIZONTAL GRINDER



H-3045 HORIZONTAL GRINDER	H-3060 HORIZONTAL GRINDER	H-4060 HORIZONTAL GRINDER
Transport Length		33' [10.06m]
Transport Height		13'1" [3.99m]
Weight		57,000 lbs [25,855kg]
Axle Weight		41,000 lbs [18,636kg]
Tongue Weight		14,500 lbs [6,577kg]
Width		9' - 10" [2.99m]
Infeed - Width (flare)		75" [1.9m]
Infeed - Width (belt)		60" [1.52m]
Infeed - Open Bed Length		20' - 10" [6.35m] to Hammermill
Infeed - Closed Bed Length		14' - 9" [4.50m] to Feed Wheel
Infeed - Loading Height		94" [2.4m]
Infeed - Belt		3/8" [9.5mm] cat style chain
Infeed - Belt Speed		0 to 70 Feet per Minute [18.3 Meters per Minute]
Belly Conveyor		59" (1.5m) wide 350pvc belt with a hydraulically driven head pulley
Stacking Conveyor	48" [1.22m] wide x 25'-6" [7.77m] long with a 12" x 50" [305mm x 1.27m] with a 10" x 50" [254mm x 1.27m]	Magnetic head pulley
Reservoirs - Hydraulic Tank		70 gallon [256 L] capacity
Reservoirs - Fuel Tank		200 gallon [757.1 L] capacity
Hammermill		60" x 30" [1.52m x 762mm]
Hammermill Cutting Diameter		30" [762mm] diameter
Hammermill Mill Speed		800 RPM
Hammermill Mill Hammers		(40) two-bolt notched fixed hammers
Hammermill Mill Shaft		7" [177.8mm] hardened alloy steel
Hammermill Hammer Rods		(6) 1-3/4" [44.5mm] alloy steel
Hammermill Support Bearings		4-7/16" [112.7mm] double row spherical
Diesel Engine		600-700HP [447-522kw]
Radio Remote		Standard