RHC 6-280 Trommel Screen

The Performance Screen for Larger







Small loaders can load the **Wildcat** without building a ramp!

- 250 cubic yards per hour with ½" screen openings (fully composted material, at 40% moisture).
- Apron chain conveyor for aggressive and consistent feeding.
- 12 cubic yard low profile hopper does not require ramps for loading.
- Tensioned screen panels can be easily changed by two people with hand tools.
- Brushes with grooming teeth remove debris from screen panels.
- 185 HP John Deere diesel engine.
- · State-of-the-art hydraulic system.
- Attached stacking conveyors.
- · All functions are variable speed.
- Solid rubber tire trommel drum drive.
- Drum driven on all four corners.
- · Set-up in less than 15 minutes.
- Options available for double folding conveyors for truck loading.
- Engine locations allows groundline servicing.

The Wildcat Trommel Screen uses tensioned screen panels, which increases open screening area. Open screening area is the key to capacity. The Wildcat RHC 6 -280 has over 320 square feet of open screening area.


RHC 6-280 Trommel Screen

Dual pumps allow proper hydraulic flow to all functions. All functions are variable speed. Controls are centrally located and clearly labeled for ease of operation.





Self-grooming brushes constantly remove debris from screen panels. The Wildcat can process material with a higher moisture content than any other trommel.



Tensioned screened panels eliminate the need for hardware to attach screen panels, maximizing open screening area, increasing production.



Optional roll tarp for dust control.



Electric units are also available.

The RHC 6-280 retains the trademark features that have made Wildcat Trommel Screens number one in the industry!



Manufacturing Company, Inc. Freeman, South Dakota 57029 USA 800-627-3954 605-925-4512 605-925-7536 Fax Home page: www.wildcatmfg.com