

THE EZ-SCREEN 2000



TRANSPORTABILITY, POWER
AND PRODUCTION, PLUS BUILT-IN
CONVEYOR, ADDS UP TO EZ VALUE



®

THE EZ-SCREEN 2000 - VITAL STATISTICS

FEATURES

- Water cooled, 41 HP Isuzu diesel (@2150 RPM) 4 cylinder with low oil/high temp shutdown
- Loading bucket size range: 1-4 yds.
- Can be equipped with grizzly bars or woven screens on top deck, and woven or piano wire screens on bottom deck
- 6' x 7'7" bolted double-deck screen box with 6" clearance between screen shaft tube and bottom decks
- Engine compartment fully enclosed, lockable, and sound-suppressed for quiet operation
- Fuel tank: 13 gallons; Hydraulic tank: 50 gallons

SPECIFICATIONS

Transport Length:	25'7"
Transport Width:	8'3"
Transport Height:	9'2"
Max. Working Height:	11'3"
Max. Stockpile Height:	8'10"
Max. Tipping Height:	10'10"
Max. Loading Width:	11'11"
Main Conveyor Width:	39"
Weight:	17,600 lbs.



Pound-for-pound, easily the best value in screeners on the market today.



More weight, more strength, more power, more versatility, yet less expensive



®

Machine pictured with optional equipment

1/01
Specifications subject to change without notice.