



◀◀◀◀◀◀◀◀◀ DZH6000

HORIZONTAL GRINDER

Attention to detail that lasts. The high-capacity, low-maintenance DZH6000 Series is ideal for virtually for any grinding application. It has been Diamond Z's best-selling horizontal grinder over the last two decades.

With a quick screen change of 20 minutes or less, power options up to 1,050hp and industry-leading production capabilities, the DZH6000 is clearly the simple choice for difficult jobs.

The DZH6000CTKT Series track-mounted horizontal grinder has all the features and capabilities of the DZH6000 with the added accessibility that comes with a track-mounted machine, allowing operation just about anywhere. The DZH6000CTKT comes with complete transport pin or axle system that easily and safely secures to the grinder so it is ready to be transported, avoiding expensive permitting fees.

FEATURES

- ◆ Fluid coupling mill drive
- ◆ Reversing fan
- ◆ Radio remote control
- ◆ Tool box
- ◆ Engine cover
- ◆ Super-screw belt lacing
- ◆ All track mounted machines come with 24" (600mm) wide pads, other options available.





SPECIFICATIONS	DZH6000	DZH6000TKT
Power	CAT® C27 1,050 HP Tier	CAT® C27 1,050 HP Tier 4
Transmission	Fluid Coupling Drive	Fluid Coupling Drive
Transport dimensions (L x W x H)	44'-2" x 12'-0" x 13'-11" (13.51m x 3.66m x 4.21m)	52'-2" x 12'-1" x 13'-8" (15.90m x 3.66m x 4.16m)
Operating dimensions (L x W x H)	68'-7" x 11'-9" x 18'-0" (20.93m x 3.62m x 5.48m)	52'-10" x 11'-11" x 14'-0" (15.88m x 3.38m x 4.27m)
Weight	93,000 lbs. (42,184.05 kg)	116,000 lbs. (52,616.67 kg)
Mill feed opening (W x H)	63" x 52" (19.20m x 15.84m)	63" x 52" (19.20m x 15.84m)
Screen area	4,320 sq. in. (27870.91 sq. cm)	4,320 sq. in. (27870.91 sq. cm)
Production	Up to 1317 TPH/524 YPH	Up to 131 TPH/524 YPH

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.