

HORIZONTAL GRINDER



H-3045 HORIZONTAL GRINDER	H-3060 HORIZONTAL GRINDER	H-4060 HORIZONTAL GRINDER
Transport Length		40' [12.85m]
Transport Height		13' - 1" [3.99m]
Weight		73,000 lbs [33,182 kg]
Axle Weight		49,250 lbs [22,386 kg]
Tongue Weight		23,750 lbs. [10,795 kg]
Width		9' - 10" [2.99m]
Infeed - Width (flare)		75" [1.9m]
Infeed - Width (belt)		60" [1.523m]
Infeed - Open Bed Length		20' [6.1m] to Hammermill
Infeed - Closed Bed Length		14' [4.3m] to Feed Wheel
Infeed - Loading Height		94" [2.4m]
Infeed - Belt		3/8" [9.5mm] cat style chain
Infeed - Belt Speed		0 to 70 Feet per Minute [18.3 Meters per Minute]
Belly Conveyor		59" [1.5m] wide 350pvc belt with a hydraulically driven head pulley
Stacking Conveyor		60" [1.52m] wide x 25'-6" [7.77m] long with a 12" x 60" [305mm x 1.52m] Magnetic head pulley
Reservoirs - Hydraulic Tank		100 gallon [378.5 L] capacity
Reservoirs - Fuel Tank		300 gallon [1,136 L] capacity
Hammermill		60" x 40" [1.52m X 1.02m]
Hammermill Cutting Diameter		40" [1.02m] diameter
Hammermill Mill Speed		675 RPM
Hammermill Mill Hammers		(40) two-bolt notched fixed hammers
Hammermill Mill Shaft		7-1/2" [190.5mm] hardened alloy steel
Hammermill Hammer Rods		(10) 1-3/4" [44.5mm] alloy steel
Hammermill Support Bearings		5-7/16" [138.1mm] double row spherical
Diesel Engine		875-1200HP [652-895kw]
Radio Remote		Standard