

MORBARK® 2600 WOOD HOG

FEATURES

- » Variable speed infeed system consists of one 22" (55.8 cm) diameter top compression feed roll with internal drive and a 57" wide x 9'7" (144.8 cm x 2.9 m) long live floor with four strands of WDH-110 chain in a staggered configuration
- » 23 ¾" x 53 ½" (60.32 cm x 134.9 cm) Hammertmill system constructed of heavy-duty 16" (40.64 cm) diameter rotor, 23 1 ½" (2.85 cm) thick two-piece laser-cut rotor plates to ensure precision and enforce steel strength. The plates are keyed on a 4 ½" (11.43 cm) diameter shaft with two 3 ¾" (8.73 cm) bearings and eight 1 ¼" (3.17 cm) hammer retaining rods. Hammertmill pattern consists of (22) 1 ¼" (3.17 cm) forged steel heavy-duty hammers, and (22) 2 ¼" (5.24 cm) wide double-edged replaceable inserts and 22 rakers

- » Automatic reversing fan system
- » Dust suppression system
- » Manually operated debris containment door
- » Discharge conveyor system consists of one hydraulically driven continuous belt with 40" (101.6 cm) wide x 17'6" (5.3 m) long belly and stacking conveyor
- » Remote control with tethered back-up system
- » Magnetized end pulley with collecting slide tray for ferrous metal removal
- » 11-HP (8.2 kW) air compressor with lockable enclosure

OPTIONS

- » Live floor equipped with slat chain
- » 12- or 16-knife chipper drum assembly
- » Single-axle option
- » 4' (1.22 m) extended infeed



Morbark Integrated Control System (MICS)

Internal Planetary Drive Feed System

Externally Adjustable Break-Away Torque Limiter



SPECIFICATIONS

US

METRIC

Length (transport)	33'8"	10.26 m
Length (operating)	33'8"	10.26 m
Height (transport)	11'6"	3.5 m
Width	7'10"	2.39 m
Gross Weight (approx.)	30,660 lbs	13,910 kg
Axle Weight (approx.)	23,920 lbs	10,850 kg
Tongue Weight (approx.)	6,720 lbs	3,050 kg
Engine	CAT	
Horsepower	275 to 300 HP	205 to 223 kW
Fuel Capacity (tank)	90 gallons	340 litres
Hydraulic Oil	92 gallons	348 litres
Infeed Opening	34" x 57"	86.4 cm x 114.8 cm
Brakes	Air	
Towing arrangement	Fifth wheel/pintle hitch	
Tracks	Optional	



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

11/10/17