



FEATURES

- ◆ Radio remote control
- ◆ Choice of screens
- ◆ Engine cover
- ◆ Fluid coupling mill drive
- ◆ Available wheeled or tracked
- ◆ Available diesel or electric
- ◆ Weights vary depending on options





SPECIFICATIONS	DZT1463B	DZT1463BT	DZT1463CTKT
Power	CAT® C27 1,050 HP/ CAT® C32 1,200 HP Tier 4	CAT® C27 1,050 HP Tier 4	CAT® C32 1,200 HP Tier 4
Transmission	Fluid Coupling Drive	Fluid Coupling Drive	Fluid Coupling Drive
Transport dimensions (L x W x H)	48'-2" x 11'-11" x 13'-11"	61'-3" x 12'-0" x 15'-6"	91'-2" x 12'-0" x 13'-11"
Operating dimensions (L x W x H)	70'-8" x 14'-0" x 14'-0"	71'-4" x 14'-0" x 18'-0"	53'-0" x 12'-0" x 15'-6"
Weight	100,000 lbs.	179,000 lbs. 135,000 lbs. w/o transporter	133,000 lbs. w/o transporter
Mill feed opening (W x H)	40" x 62"	40" x 62"	40" x 62"
Screen area	6,795 sq. in.	6,795 sq. in.	6,795 sq. in.
Production	Up to 135 TPH/600 YPH	Up to 135 TPH/600 YPH	Up to 135 TPH/600 YPH

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.