


# MORBARK 6600 TRACK WOOD HOG

## BENEFITS


- An aggressive, productive track grinder from the leading manufacturer of industrial grade grinding equipment.
- Process clearing debris, yard waste, storm debris and other mixed woody feedstocks into saleable products.
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.



**Morbark Integrated Control Systems**  
The ultimate diagnostic system; monitors hydraulic pressures, temperatures, clutch systems and engine efficiency while automatically adjusting to maximize performance.



**GRATE ACCESS**  
Hydraulic hinged door allows quick and easy access for changing grates.



**FEED SYSTEM**  
Internal planetary drive on feed wheel with no chains and sprockets means lower maintenance, more torque and better durability.



**TRACK SYSTEM**  
330L Caterpillar Undercarriage with double grouser pads, with 18" ground clearance

## SPECIFICATIONS

Note: Specifications may vary with equipment options

11122010

### GENERAL

Length (transport).....	41'7"
Length (operating).....	54'10"
Height .....	11'10"
Width .....	11'10"
Gross weight .....	109,120 lbs.
Engine.....	CAT or Cummins
Horsepower.....	860 HP to 1,200 HP
Fuel capacity (tank) .....	390 gallons
Hydraulic oil capacity.....	335 gallons
Morbark Integrated Control Systems	
Hydraulically operated debris containment door	
Dust suppression system	

### INFEED SYSTEM

66" x 50" infeed opening  
10 cubic yard infeed hopper  
Variable speed infeed system consists of one 36" diameter top compression feed roll with internal drive and a 17' x 64" live floor equipped with five strands of WDH-120 chain in a staggered configuration with dual drives and 4'7" long hydraulically folding infeed extension

### HAMMERMILL AND GRATES

42" diameter x 66 5/8" hammermill with a 42" tip swing  
Heavy duty 28" diameter rotors, (18) 1 3/8" thick rotor plates on 8 1/4" diameter rotor shaft with 5 3/16" bearings, (8) 2 1/2" hammer retaining rods, (30) 2 1/4" thick balanced forged steel fixed teeth insert hammers equipped with (30) 3 5/8" wide double edged replacement hammerhead inserts and (30) rakers. Four sec-

tions of 1" thick wear form steel heavy duty grates

### DISCHARGE SYSTEM

Discharge system consisting of a hydraulically driven, horizontal 48" long aggregate belly belt conveyor discharging onto a 40" stacking conveyor  
Hydraulic fold for transport  
Stacking height 19'

### OPTIONS

Caterpillar 330EL undercarriage  
Variety of grate sizes available  
Hydraulic reversing fan  
Magnetized end pulley  
11 HP air compressor  
Hydraulic rod puller  
Externally adjustable torque limiter



800-831-0042 989-866-2381  
[www.morbark.com](http://www.morbark.com)