

C12

Mobile Cone Crusher



Hopper/Feeder

- Hydraulic folding sides and rear hopper doors
- Ground-level controls
- 4.5 cubic yard (3.4 cubic meter) hopper capacity
- Eye sensor to control feed material

Cone Crusher

- Direct drive through V-belts
- Hydraulic adjustment
- Automatic overload protection
- Up to 165tph (150mtp) capacity

Main Conveyor

- Hydraulically folds for transport
- 36" (914mm) belt width
- 9' (2,743mm) discharge height
- Speed wheel to stop machine if conveyor stops

Power Unit

- Volvo Penta D5 172hp (129kw), EU Stage IV or V, EPA Tier 3 or 4F
- CAT C4.4 172hp (129kw) EU Stage IV or V, EPA Tier 3 or 4F
- 111 gal (420L) fuel tank

Options

- Dust suppression
- Dust covers on main conveyor
- Radio remote
- Belt scales
- Recirculation closed loop system
- Refuelling pump
- Feed hopper extensions
- Automatic greasing

Physical/Operating Characteristics

Dimension	Standard	Metric
Operating Length	41' 11"	12.8m
Operating Width	11' 10"	3.6m
Operating Height	11' 9"	3.6m
Travel Length	34' 7"	10.6m
Travel Width	7' 5"	2.3m
Travel Height	9' 10"	3m
Unit Weight	49,200lb	22,300kg
Feed Height (Front Feed)	9' 10"	3.1m

