

HORIZONTAL GRINDER



H-3045 HORIZONTAL GRINDER	H-3060 HORIZONTAL GRINDER	H-4060 HORIZONTAL GRINDER
Transport Length		31' - 4" [9.55m]
Transport Height		13' - 6" [4.11m]
Weight		44,000 lbs [19,958kg]
Axle Weight		33,000 lbs [14,968kg]
Tongue Weight		11,000 lbs [4,989kg]
Width		8' - 6" [2.59m]
Infeed - Width (flare)		60" [1.52m]
Infeed - Width (belt)		45" [1.14m]
Infeed - Open Bed Length		18' - 10" [5.74m] to Hammermill
Infeed - Closed Bed Length		12' - 9" [3.88m] to Feed Wheel
Infeed - Loading Height		93" [2.36m]
Infeed - Belt		3/8" [9.5mm] cat style chain
Infeed - Belt Speed		0 to 50 Feet per Minute [15.2 Meters per Minute]
Belly Conveyor		44" (1.1m) wide 350pvc belt with a hydraulically driven head pulley
Stacking Conveyor	48" [1.22m] wide x 25'-6" [7.77m] long with a 10" x 50" [254mm x 1.27m] Magnetic head pulley	
Reservoirs - Hydraulic Tank		70 gallon [256 L] capacity
Reservoirs - Fuel Tank		130 gallon [492.1 L] capacity
Hammermill		45" x 30" [1.14m x 762mm]
Hammermill Cutting Diameter		30" [762mm] diameter
Hammermill Mill Speed		800 RPM
Hammermill Mill Hammers		(30) two-bolt notched fixed hammers
Hammermill Mill Shaft		7" [177.8mm] hardened alloy steel
Hammermill Hammer Rods		(6) 1-3/4" [44.5mm] alloy steel
Hammermill Support Bearings		4-7/16" [112.7mm] double row spherical
Diesel Engine		520-600HP [387-447kw]
Radio Remote		Standard