




FW 220 SXL - FW 750 SX



Standard
winding direction:
counterclockwise



		FW 220SXL	FW 250SX	FW 250SXL	FW 300SX	FW 300SXL	FW 350SX	FW 350SXL	FW 450SX	FW 450SXL	FW 550SX	FW 750SX
1ST LINE PULL	daN	2050	2325	2325	3100	3100	3600	3600	4300	4300	5500	6500
LAST LINE PULL	daN	1370	1560	1560	2200	2200	2550	2550	2820	2820	4200	5200
ROPE LAYERS	n°	5	4	4	5	5	5	5	5	5	5	4
ROPE SIZE	mm	10	11	11	13	13	14	14	15	15	16	18
ROPE LENGHT	m	140	50	98	70	136	62	128	58	120	128	88
ROPE SPEED	m/min	30	28	28	34	34	32	32	30	30	38	36
WEIGHT	kg	100	87	102	129	155	136	160	140	165	340	360
MAX FLOW	l/min	60	60	60	75	75	75	75	75	75	130	130
PRESSURE	bar	160	180	180	175	175	185	185	195	195	260	280
MOTOR	cc/rev	100	100	100	100	100	100	100	100	100	45	45
ENGINE TORQUE	Nm	210	230	230	220	220	220	220	220	220	150	160
MAX TORQUE ON THE DRUM	Nm	2600	2700	2700	5500	5500	5500	5500	5500	5500	12300	12300
MAX BACK PRESSURE ON RETURN LINE	bar	2	2	2	2	2	2	2	2	2	2	2
GEAR RATIO		13,8	13,8	13,8	26,8	26,8	26,8	26,8	26,8	26,8	90,7	90,7
FULL OPENING BRAKE PRESSURE	bar	25	25	25	33	33	33	33	33	33	19	19
A	mm	372	190	372	213	413	213	413	213	413	352	352
B	mm	560	380	560	495	690	495	690	495	690	700	700
Ø C	mm	220	220	220	250	250	250	250	250	250	323	323
D	mm	322	322	322	404	404	404	404	404	404	500	500
E	mm	384	384	384	470	490	470	490	470	490	580	580
Ø F	mm	322	322	322	400	400	400	400	400	400	500	500
G	mm	364	170	364	245	445	245	445	245	445	380	380
H	mm	250	250	250	360	360	360	360	360	360	410	410
Ø I	mm	15	15	15	19	19	19	19	19	19	19	19

Products not suitable for lifting people

